



### Features A: Digital Signage

1. Android OS 6.01 system, Support website visiting;
2. Auto upload videos or photos from the software installed in the PC after connecting internet via wifi, even displays are in different places;
3. Support remote content update, upload, delete, support OSD, VOD, loop playback;
4. Support Split screen, Rolling text;
5. Support HD Video resolution: 1920x1080;
6. Support Calendar, Clock; 7. Support 3rd party APK installation;
8. Media files Supported: datob/ mpg/ divx(.avi)/ bmp/ jpgtf/ flash.

### Features B: Auto Dispenser

1. Auto Dispense: Auto Dispense by Sensor, touch free to avoid cross infection;
  2. Power Supply: AC adapter;
  3. Auto Identify: Identify the disinfectant automatically, only work for the authorized one;(Optional)
  4. Dispensing Life: The life of our dispenser is more than 650000 times;
  5. Soap/Disinfectant Bottle
- Pump: Standard pump for Liquid, Foam, and Gel is optional. Each drop is about 1ML for Gel; 0.4ML for Foam; 2ML for Liquid

## Features C: Face recognition

1. Support face recognition and comparison while wearing a mask
2. Using industrial-grade binocular wide dynamic camera, night infrared, LED dual fill light

## Features D: Body temperature measurement

1. Support human body temperature detection, temperature display.
2. 1 meter ultra-distant body temperature detection, 0.2°C error.
3. Support and automatic alarm for abnormal body temperature, second-level detection speed, real-time export of attendance temperature measurement data



## Specification

### Panel

Panel Size	21.5"
Display Ratio	16:9
Resolution	1920(H)*1080(V)
Active Area	476.64(H)*268.11(V)
Brightness	300cd/m <sup>2</sup>
Contrast Ratio	1000:1
Viewing Angle	89/89/89/89

### Touch

10 point Capacitive Touch

### Power

Voltage	AC 100-240V	50-60Hz
Consumption	≤1W (Standby)	35W (Working)



## 21.5" inch hand sanitiser digital signage

### Android Solution

CPU	RK3288
RAM	2G
Memory	8G
OS	Android 6.01/7.1
Network	wifi/internal//3G/4G(Optional)

### Speaker

Built-in 2\*10W

### Environment

Working temperature	0°C- 40 °C
Storage temperature	-20°C- 60°C
Working humidity	10%-90%

### I/O

HDMI	*1
VGA	*1
RJ-45	*1
USB	*2
Mic In	*1
Line Out	*1

### Packing

Sample	Wooden case
Bulk order	Carton box(2CM Thickness) +Foam Inside